



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - France

SAFETY DATA SHEET

DUOL SATIN BLANC 0001

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : DUOL SATIN BLANC 0001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Consumer use
Uses advised against
None

Product use : Solvent borne coating for exterior use.

1.3 Details of the supplier of the safety data sheet

Akzo Nobel Decorative Paints France
Département : Levis
Z.I. "Les Bas Prés"
C.S. 70113
60761 Montataire Cedex
France
N° Téléphone : 03.44.64.91.00
N° Télécopie : 03.44.64.91.90
www.levispeintures.com

e-mail address of person responsible for this SDS : fds.fr@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Numéro ORFILA (INRS) : + 33 (0)1 45 42 59 59

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]


Flam. Liq. 3, H226
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapor.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

- General : P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.
- Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
- Response : Not applicable.
- Storage : P403 + P235 - Store in a well-ventilated place. Keep cool.
- Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
- Supplemental label elements : Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

- Containers to be fitted with child-resistant fastenings : Not applicable.
- Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥25 - ≤50	Carc. 2, H351 (inhalation)	-	[1] [*]
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	REACH #: 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9 Index: 649-327-00-6	≤11	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	-	[1]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5	≤3.6	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	-	[1]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119456620-43 EC: 926-141-6	≤3.6	Asp. Tox. 1, H304 EUH066	-	[1]
Naphtha (petroleum), hydrotreated heavy	REACH #: 01-2119486659-16 EC: 265-150-3 CAS: 64742-48-9 Index: 649-327-00-6	≤1	Asp. Tox. 1, H304 EUH066	-	[1]
Reaction mass of ethylbenzene and xylene	REACH #: 01-2119488216-32 EC: 905-588-0	<1	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
IPBC	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
(2-methoxymethylethoxy) propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤0.3	Not classified.	-	[2]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361	-	[1]

SECTION 3: Composition/information on ingredients					
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a physical, health or environmental hazard
 - [2] Substance with a workplace exposure limit
 - [*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.
- Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 4: First aid measures

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria		
Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Reaction mass of ethylbenzene and xylene	Ministry of Labor (France, 3/2020). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL: 442 mg/m³ 15 minutes. Form: Risk for sensitisation STEL: 100 ppm 15 minutes. Form: Risk for sensitisation TWA: 221 mg/m³ 8 hours. Form: Risk for sensitisation TWA: 50 ppm 8 hours. Form: Risk for sensitisation
(2-methoxymethylethoxy)propanol	Ministry of Labor (France, 12/2021). [(2-methoxymethylethoxy)-propanol] Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 50 ppm 8 hours. TWA: 308 mg/m³ 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	DNEL	Long term Inhalation	0.41 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	1.9 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	178.57 mg/m³	General population	Local
	DNEL	Long term Oral	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	640 mg/m³	General population	Local
	DNEL	Long term Inhalation	837.5 mg/m³	Workers	Local
	DNEL	Short term Inhalation	1066.67 mg/m³	Workers	Local
	DNEL	Short term Inhalation	1152 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	1286.4 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	0.41 mg/m³	General	Systemic
	DNEL	Long term Inhalation	0.41 mg/m³	General	Systemic

SECTION 8: Exposure controls/personal protection

heavy	DNEL	Inhalation Long term	1.9 mg/m³	population Workers	Systemic
	DNEL	Inhalation Long term	178.57 mg/m³	General population	Local
	DNEL	Oral Long term	300 mg/kg bw/day	General population	Systemic
	DNEL	Dermal Long term	300 mg/kg bw/day	General population	Systemic
	DNEL	Dermal Long term	300 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Short term	640 mg/m³	General population	Local
	DNEL	Inhalation Long term	837.5 mg/m³	Workers	Local
	DNEL	Inhalation Short term	1066.67 mg/m³	Workers	Local
	DNEL	Inhalation Short term	1152 mg/m³	General population	Systemic
	DNEL	Inhalation Short term	1286.4 mg/m³	Workers	Systemic
Reaction mass of ethylbenzene and xylene	DNEL	Oral Long term	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Inhalation Long term	14.8 mg/m³	General population	Systemic
	DNEL	Inhalation Long term	77 mg/m³	Workers	Systemic
	DNEL	Dermal Long term	108 mg/kg bw/day	General population	Systemic
	DNEL	Dermal Long term	180 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Short term	289 mg/m³	Workers	Local
	DNEL	Inhalation Short term	289 mg/m³	Workers	Systemic
	DNEL	Inhalation Long term	0.023 mg/m³	Workers	Systemic
IPBC	DNEL	Inhalation Short term	0.07 mg/m³	Workers	Systemic
	DNEL	Inhalation Short term	1.16 mg/m³	Workers	Local
	DNEL	Inhalation Long term	1.16 mg/m³	Workers	Local
	DNEL	Dermal Long term	2 mg/kg bw/day	Workers	Systemic
	DNEL	Oral Long term	36 mg/kg bw/day	General population	Systemic
	DNEL	Inhalation Long term	37.2 mg/m³	General population	Systemic
(2-methoxymethylethoxy)propanol	DNEL	Dermal Long term	121 mg/kg bw/day	General population	Systemic
	DNEL	Dermal Long term	283 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Long term	308 mg/m³	Workers	Systemic
	DNEL	Oral Long term	0.34 mg/kg bw/day	General population	Systemic
propylidynetrimethanol	DNEL	Dermal Long term	0.34 mg/kg bw/day	General population	Systemic
	DNEL	Inhalation Long term	0.58 mg/m³	General	Systemic

SECTION 8: Exposure controls/personal protection					
	DNEL	Inhalation Long term Dermal	0.94 mg/ kg bw/day	population Workers	Systemic
	DNEL	Long term Inhalation	3.3 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
manganese neodecanoate	Fresh water	85.3 µg/l	Assessment Factors
	Marine water	2.7 µg/l	Assessment Factors
	Sewage Treatment Plant	121.3 mg/l	Assessment Factors
	Fresh water sediment	230.6 mg/kg dwt	Assessment Factors
	Marine water sediment	23.06 mg/kg dwt	Assessment Factors
	Soil	167.33 mg/kg dwt	Assessment Factors

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better.
Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : White.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : 149°C (300.2°F)
- Flammability** : Not available.
- Lower and upper explosion limit** : Greatest known range: Lower: 1.4% Upper: 7.6% (hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics)
- Flash point** : Closed cup: 38°C (100.4°F) [Pensky-Martens]
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	>200	>392	
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	280 to 470	536 to 878	
Naphtha (petroleum), hydrotreated heavy	280 to 470	536 to 878	

- Decomposition temperature** : Not available.
- pH** : Not applicable. [DIN EN 1262]
- Viscosity** : Kinematic (room temperature): 1257 mm²/s [DIN EN ISO 3219]
Kinematic (40°C): 201 mm²/s [DIN EN ISO 3219]
- Solubility(ies)** :

SECTION 9: Physical and chemical properties

Media	Result
cold water	Not soluble [OECD (TG 105)]

Partition coefficient: n-octanol/ water : Not applicable.

Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	0.75 to 2.25	0.1 to 0.3				
Naphtha (petroleum), hydrotreated heavy	0.75 to 2.25	0.1 to 0.3				
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	0.15	0.02				

Relative density : 1.271

Vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10 µm : 0

9.2 Other information

Minimum ignition energy (mJ) : Not available.

Fundamental burning velocity : Not applicable.

SADT : Not available.

Heat of combustion : Not available.

Aerosol product

Type of aerosol : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	LC50 Inhalation Vapor	Rat	8500 mg/m³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
Naphtha (petroleum), hydrotreated heavy	LC50 Inhalation Vapor	Rat	8500 mg/m³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
IPBC (2-methoxymethylethoxy) propanol	LD50 Oral	Rat	1470 mg/kg	-
	LD50 Dermal	Rabbit	10 mL/kg	-
propylidynetrimethanol	LD50 Oral	Rat	5.5 mL/kg	-
	LD50 Oral	Rat	5400 µL/kg	-
	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	N/A	N/A	N/A	N/A	166.7
Reaction mass of ethylbenzene and xylene	N/A	1100	N/A	11	N/A
IPBC	500	N/A	N/A	N/A	0.5

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Reaction mass of ethylbenzene and xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

SECTION 11: Toxicological information

(2-methoxymethylethoxy) propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	Category 3	-	Narcotic effects
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	-	Narcotic effects
Reaction mass of ethylbenzene and xylene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Reaction mass of ethylbenzene and xylene	Category 2	-	-
IPBC	Category 1	-	larynx

Aspiration hazard

Product/ingredient name	Result
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrotreated heavy	ASPIRATION HAZARD - Category 1
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

SECTION 11: Toxicological information

Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.
General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide Reaction mass of ethylbenzene and xylene IPBC	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 956 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.16 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 2920 ppb Marine water	Crustaceans - Neomysis mercedis - Adult	48 hours
	Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 95 ppb Marine water	Fish - Oncorhynchus kisutch - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 100 ppb Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 72 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours

SECTION 12: Ecological information

propylidynetrimethanol	Acute LC50 67 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days
	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	-	10 to 2500	high
Naphtha (petroleum), hydrotreated heavy	-	10 to 2500	high
Reaction mass of ethylbenzene and xylene	3.12	8.1 to 25.9	low
(2-methoxymethylethoxy) propanol	0.004	-	low
propylidynetrimethanol	-0.47	<1	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)



The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number or ID number	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 
14.4 Packing group	III	III
14.5 Environmental hazards	No.	No.

Additional information

SECTION 14: Transport information

ADR/RID	: Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1. Tunnel code (D/E)
IMDG	: Emergency schedules F-E, _S-E_ Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.
14.6 Special precautions for user	: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
EU Regulation (EC) No. 1907/2006 (REACH)	
Annex XIV - List of substances subject to authorization	
Annex XIV	None of the components are listed.
Substances of very high concern	None of the components are listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: Not available.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substances (1005/2009/EU)	Not listed.
Fire point	Not listed.
Persistent Organic Pollutants	Not listed.
Seveso Directive	

SECTION 15: Regulatory information

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
titanium dioxide	France Occupational Exposure Limits	titane (dioxyde de) en Ti	Carc. C2	-

Biocidal products regulation

Social Security Code, Articles L 461-1 to L 461-7	:	titanium dioxide	RG 25
	:	hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, <2% of aromatics	RG 84
	:	Naphtha (petroleum), hydrotreated heavy	RG 84
	:	Reaction mass of ethylbenzene and xylene (2-methoxymethylethoxy)propanol	RG 4bis, RG 84
	:		RG 84
Reinforced medical surveillance	:	Decree n ° 2012-135 of January 30, 2012 relating to the organization of occupational medicine: not applicable	

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	:	ATE = Acute Toxicity Estimate
	:	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	:	DMEL = Derived Minimal Effect Level
	:	DNEL = Derived No Effect Level
	:	EUH statement = CLP-specific Hazard statement
	:	N/A = Not available
	:	PBT = Persistent, Bioaccumulative and Toxic
	:	PNEC = Predicted No Effect Concentration
	:	RRN = REACH Registration Number
	:	SGG = Segregation Group
	:	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

SECTION 16: Other information	
Classification	Justification
Flam. Liq. 3, H226 Aquatic Chronic 3, H412	On basis of test data Calculation method

Full text of abbreviated H statements

H226 H302 H304 H312 H315 H317 H318 H319 H331 H332 H335 H336 H351 H361 H372 H373 H400 H410 H412 EUH066	Flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Toxic if inhaled. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
--	--

Full text of classifications [CLP/GHS]

Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Carc. 2 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 3 Repr. 2 Skin Irrit. 2 Skin Sens. 1 STOT RE 1 STOT RE 2 STOT SE 3	ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 TOXIC TO REPRODUCTION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
--	---

Date of printing : 2-7-2024
Date of issue/ Date of revision : 2-7-2024
Date of previous issue : 26-1-2024
Version : 1.01
Unique ID : DA7DF488320C1EEEEAF8AB3EBE542C2FA
Notice to reader

SECTION 16: Other information

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.