

# SAFETY DATA SHEET

AMBIANCE LAK MAT MIX BASE WHITE

## **SECTION 1: Identification of the substance/mixture and of the company/** undertaking

## 1.1 Product identifier Product name

: AMBIANCE LAK MAT MIX BASE WHITE

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Professional use Consumer use		
	Uses advised against	
None		

## **Product use**

: Waterborne coating for interior use.

## 1.3 Details of the supplier of the safety data sheet

Akzo Nobel Decorative Paints France Département : Levis Z.I. "Les Bas Prés" C.S. 70113 60761 Montataire Cedex France N° Téléphone : 03.44.64.91.00 N° Télécopie : 03.44.64.91.90 www.levispeintures.com

e-mail address of person : fds.fr@akzonobel.com responsible for this SDS

## 1.4 Emergency telephone number

## National advisory body/Poison Center

 Telephone number
 : Numéro ORFILA (INRS) : + 33 (0)1 45 42 59 59



## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture				
Product definition	: Mixture			
Classification according to Not classified.	Regulation (EC) No. 1272/2008 [CLP/GHS]			
The product is not classified a	as hazardous according to Regulation (EC) 1272/2008 as amended.			
•	iled information on health effects and symptoms.			
2.2 Label elements				
Signal word	: No signal word.			
Hazard statements	: No known significant effects or critical hazards.			
Precautionary statements				
General	<ul> <li>P102 - Keep out of reach of children.</li> <li>P101 - If medical advice is needed, have product container or label at hand.</li> </ul>			
Prevention	: P262 - Do not get in eyes, on skin, or on clothing.			
Response	: P312 - Call a doctor if you feel unwell.			
Storage	: Not applicable.			
Disposal	<ul> <li>P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.</li> </ul>			
Supplemental label elements	: Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 1,2-benzisothiazol-3(2H)-one, octhilinone (ISO) and CMIT/MIT(3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.			
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.			
Special packaging requirements				
Containers to be fitted with child-resistant fastenings	: Not applicable.			
Tactile warning of danger	: Not applicable.			
2.3 Other hazards				
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.			
Other hazards which do not result in classification	: None known.			
SECTION 3: Composition/information on ingredients				

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

: Mixture



AMBIANCE LAK MAT MIX BASE WHITE

#### SECTION 3: Composition/information on ingredients Specific Conc. % Product/ingredient name Identifiers Classification Туре Limits, M-factors and ATEs ≥20 - ≤25 Carc. 2, H351 titanium dioxide REACH #: [1] [\*] 01-2119489379-17 (inhalation) EC: 236-675-5 CAS: 13463-67-7 Not classified. (2-methoxymethylethoxy) REACH #: ≤3 [2] 01-2119450011-60 propanol EC: 252-104-2 CAS: 34590-94-8 2,4,7,9-tetramethyldec-REACH #: <1 Eye Dam. 1, H318 [1] 5-yne-4,7-diol 01-2119954390-39 Skin Sens. 1B, H317 EC: 204-809-1 Aquatic Chronic 3, H412 CAS: 126-86-3 1,2-benzisothiazol-3(2H)-EC: 220-120-9 < 0.01 Acute Tox. 4, H302 ATE [Oral] = 500 [1] CAS: 2634-33-5 Acute Tox. 2, H330 one mg/kg ATE [Inhalation Skin Irrit. 2, H315 (dusts and mists)] Eye Dam. 1, H318 = 0.05 mg/l Skin Sens. 1, H317 Aquatic Acute 1, H400 Skin Sens. 1, H317: Aquatic Chronic 2, C ≥ 0.05% H411 M [Acute] = 10 OIT EC: 247-761-7 < 0.001 Acute Tox. 3, H301 ATE [Oral] = 125 [1] CAS: 26530-20-1 Acute Tox. 3, H311 mg/kg Index: 613-112-00-5 Acute Tox. 2, H330 ATE [Dermal] = Skin Corr. 1, H314 311 mg/kg Eye Dam. 1, H318 ATE [Inhalation Skin Sens. 1A, H317 (dusts and mists)] Aquatic Acute 1, H400 = 0.27 mg/l Skin Sens. 1, H317: Aquatic Chronic 1, H410 C ≥ 0.0015% EUH071 M [Acute] = 100 M [Chronic] = 100 < 0.001 Acute Tox. 3, H301 ATE [Oral] = 100 CMIT/MIT(3:1) REACH #: [1] 01-2120764691-48 Acute Tox. 2, H310 mg/kg Acute Tox. 2, H330 EC: 911-418-6 ATE [Dermal] = 50 Skin Corr. 1C, H314 CAS: 55965-84-9 mg/kg ATE [Inhalation Index: 613-167-00-5 Eye Dam. 1, H318 (dusts and mists)] Skin Sens. 1A, H317 Aquatic Acute 1, H400 = 0.05 mg/l Skin Corr. 1C, Aquatic Chronic 1, H410 H314: C ≥ 0.6% EUH071 Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 : 28-1-2024 Date of issue/Date of revision Version :1 **AkzoNobel** Date of previous issue : No previous validation 3/17

## **SECTION 3: Composition/information on ingredients**

See Section 16 for	
the full text of the H	
statements declared	
above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

## 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 1,2-benzisothiazol-3(2H)-one, octhilinone (ISO), CMIT/MIT(3:1). May produce an allergic reaction.

## Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

## 4.3 Indication of any immediate medical attention and special treatment needed

Date of issue/Date of revision	: 28-1-2024	Version : 1	
Date of previous issue	: No previous validation	4/17	AkzoNobel

AMBIANCE LAK MAT MIX BASE WHITE

<b>SECTION 4: First aid</b>	measures			
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>			
Specific treatments	ic treatments : No specific treatment.			
<b>SECTION 5: Firefight</b>	ing measures			
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.			
Unsuitable extinguishing media	: None known.			
5.2 Special hazards arising fr	rom the substance or mixture			
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.			
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides			
5.3 Advice for firefighters				
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.			
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.			

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## 6.3 Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop
	up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry
	material and place in an appropriate waste disposal container. Dispose of via a
	licensed waste disposal contractor.



## **SECTION 6: Accidental release measures**

Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.	
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)		
Recommendations	:	Not available.
Industrial sector specific solutions	:	Not available.
Solutions		

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

## 8.1 Control parameters

## **Occupational exposure limits**

		Exp	osure limit values	
		Ministry of Labor (France, 12/2021). [(2-methoxymethylethoxy) -propanol] Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.		
Recommended monitoring procedures	<ul> <li>g : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effect of the ventilation or other control measures and/or the necessity to use response equipment. Reference should be made to monitoring standards the following: European Standard EN 689 (Workplace atmospheres - Guide the assessment of exposure by inhalation to chemical agents for compariso limit values and measurement strategy) European Standard EN 14042 (W atmospheres - Guide for the application and use of procedures for the assessment of exposure by inhalation and use of procedures for the assessment of exposure by the application and use of procedures for the assessment of exposure by the application and use of procedures for the assessment of exposure by the application and use of procedures for the assessment of exposure by the application and use of procedures for the assessment of exposure by the assessment exposure by the assessment exposure by the assessment exposure</li></ul>		effectiveness respiratory Irds, such as Guidance for arison with (Workplace	
Date of issue/Date of revision	: 28-1-2024	Ver	sion :1	
Date of previous issue	te of previous issue : No previous validation		7 A	kzoNobel

AMBIANCE LAK MAT MIX BASE WHITE

## **SECTION 8: Exposure controls/personal protection**

of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
(2-methoxymethylethoxy)propanol	DNEL	Long term Oral	36 mg/kg	General	Systemic
	DNEL	Long term	bw/day 37.2 mg/m³	population General	Systemic
	DINCL	Inhalation	57.2 mg/m	population	Oysternic
	DNEL	Long term Dermal	121 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	308 mg/m <sup>3</sup>	Workers	Systemic
2,4,7,9-tetramethyldec-5-yne-4,7-diol	DNEL	Long term Oral	0.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term	0.43 mg/m <sup>3</sup>	General	Systemic
		Inhalation	0.5	population	O unter a la
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	0.75 mg/	General	Systemic
		Shart tarm Darmal	kg bw/day	population	Sustamia
	DNEL	Short term Dermal	0.75 mg/ kg bw/day	General population	Systemic
	DNEL	Short term	1.29 mg/m <sup>3</sup>	General	Systemic
		Inhalation	Ū	population	5
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.76 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	5.28 mg/m <sup>3</sup>	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic
CMIT/MIT(3:1)	DNEL	Long term	0.02 mg/m <sup>3</sup>		Local
	DNEL	Inhalation Long term	0.02 mg/m³	population Workers	Local
	DNEL	Inhalation Short term	0.04 mg/m <sup>3</sup>		Local
	DNEL	Inhalation Short term	0.04 mg/m <sup>3</sup>	population Workers	Local
	האיבי	Inhalation	0.00 mm	Conoral	Sustamic
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/	General	Systemic
			kg bw/day	population	

## <u>PNECs</u>

## **SECTION 8: Exposure controls/personal protection**

No PNECs available.

8.2 Exposure controls		
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.	Э
Individual protection measu	<u>es</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.	
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicate this is necessary.	
	For all types of exposure, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.	
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.	
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.	;
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importan aspects of use.	
	Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Wear a Approved/certified disposable particulate dust mask.	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	



## **SECTION 9: Physical and chemical properties**

:

:

:

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: White.
Odor	: Characteristic.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flammability	: Not available.
Lower and upper explosion limit	: Greatest known range: Lower: 1.1% Upper: 14% ((2-methoxymethylethoxy) propanol)
Flash point	: Not available.

#### Auto-ignition temperature

Ingredient name	°C	°F	Method
2-[(2-methoxy-4-nitrophenyl)azo]-N- (2-methoxyphenyl)-3-oxobutyramide	180	356	VDI 2263
(2-methoxymethylethoxy)propanol	207	404.6	EU A.15
tributylamine	210	410	EU A.15

## **Decomposition temperature** : Not available.

рН	: 8 [Conc. (% w/w): 100%] [DIN EN 1262]
Viscosity	: Kinematic (room temperature): 1260 mm²/s [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

## Solubility(ies)

Media	Result
cold water	Soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable. water

## Vapor pressure

	V	apor Pressu	r Pressure at 20°C		Vapor pressure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ammonia	360.03	48				
triethylamine	54	7.2				
ethanol	42.95	5.7				
Relative density	: 1.27	7				
Vapor density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				
Percentage of particles with aerodynamic diameter $\leq 10$						

μm

## 9.2 Other information

Date of issue/Date of revision	: 28-1-2024	Version :1	
Date of previous issue	: No previous validation	9/17	AkzoNobel

SECTION 9: Physical and chemical properties			
Minimum ignition energy (m.	Not available.		
Fundamental burning velocities	Not applicable.		
SADT	Not available.		
Heat of combustion	Not available.		
Aerosol product			
Type of aerosol	Not applicable.		
<b>SECTION 10: Stability</b>	d reactivity		
10.1 Reactivity	o specific test data related to reactivity available for this product or its ingred	dients.	
10.2 Chemical stability	e product is stable.		
10.3 Possibility of	nder normal conditions of storage and use, hazardous reactions will not occ	our.	
hazardous reactions			
10.4 Conditions to avoid	o specific data.		
10.5 Incompatible materials	o specific data.		
•			
10.6 Hazardous	nder normal conditions of storage and use, hazardous decomposition produ	ucts	
decomposition products	ould not be produced.		

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 1,2-benzisothiazol-3(2H)-one, octhilinone (ISO), CMIT/MIT(3:1). May produce an allergic reaction.

## Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(2-methoxymethylethoxy) propanol	LD50 Dermal	Rabbit	10 mL/kg	-
	LD50 Oral	Rat	5.5 mL/kg	-
	LD50 Oral	Rat	5400 uL/kg	-
1,2-benzisothiazol-3(2H)- one	LD50 Oral	Mouse	1150 mg/kg	-
	LD50 Oral	Rat	1020 mg/kg	-
OIT	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

Date of issue/Date of revision	: 28-1-2024	Version : 1	
Date of previous issue	: No previous validation	10/17	AkzoNobel

## **SECTION 11: Toxicological information**

: Not available. **Conclusion/Summary** 

## Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one	500	N/A	N/A	N/A	0.05
OIT	125	311	N/A	N/A	0.27
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
(2-methoxymethylethoxy)	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
propanol	Skin - Mild irritant	Rabbit		mg 500 mg	_
2,4,7,9-tetramethyldec-	Eyes - Severe irritant	Rabbit	-	0.1 MI	-
5-yne-4,7-diol				-	
0.T	Skin - Mild irritant	Rabbit	-	0.5 gm	-
OIT	Eyes - Severe irritant	Rabbit	-	100 mg	-
Conclusion/Summary	: Not available.				
<u>Sensitization</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
<u>Carcinogenicity</u>					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
<u>Teratogenicity</u>					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>ty (single exposure)</u>				
Not available.					
Specific target organ toxicit	v (repeated exposure)				
Not available.	<u>,</u>				
Appiration bozard					
Aspiration hazard					
Not available.					
nformation on the likely	: Not available.				
outes of exposure					
otential acute health effects					
Eye contact	: No known significant effect				
Inhalation	: No known significant effect				
Skin contact	: No known significant effect				
Ingestion	: No known significant effec	ts or critical haza	rds.		
ymptoms related to the phy	sical, chemical and toxicolo	gical characteris	<u>stics</u>		
Eye contact	: No specific data.				
Inhalation	: No specific data.				
ate of issue/Date of revision	: 28-1-2024	Vers	ion :1		
ate of previous issue	: No previous validation	11/1			AkzoNobe

# SECTION 11: Toxicological information Skin contact : No specific data. Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

## 11.2 Information on other hazards

## 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

No additional information.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
		dubia	
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
OIT	Acute EC10 0.000224 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.084 mg/l	Algae - Desmodesmus	72 hours
		subspicatus	
Date of issue/Date of revision	: 28-1-2024	Version :1	
Date of previous issue	: No previous validation	12/17	AkzoNobel

## **SECTION 12: Ecological information**

Acute EC50 0.00129 mg/l	Algae - Navicula peliculosa	48 hours
Acute EC50 0.42 mg/l	Daphnia	48 hours
Acute EC50 107 ppb Fresh water	Daphnia - Daphnia magna	48 hours
Acute EC50 180 ppb Fresh water	Daphnia - Daphnia magna	48 hours
Acute EC50 320 ppb Fresh water	Daphnia - Daphnia magna	48 hours
Acute LC50 154 ppb Fresh water	Fish - Notemigonus crysoleucas	96 hours
Acute LC50 47 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
Acute LC50 50 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
Acute LC50 65.5 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
Acute LC50 140 ppb Fresh water	Fish - Pimephales promelas	96 hours
Chronic NOEC 8.5 ppb	Fish - Pimephales promelas	35 days

**Conclusion/Summary** : Not available.

## 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

## 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
(2-methoxymethylethoxy) propanol	0.004	-	low
OIT	2.45	-	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

## 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## 12.6 Endocrine disrupting properties

Not available.

## 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

<u>Product</u> Methods of disposal		tions and any by-products shoι	uld at all times comply
	any regional local authority re products via a licensed waste	ronmental protection and waste quirements. Dispose of surplu disposal contractor. Waste sl fully compliant with the require	is and non-recyclable hould not be disposed of
Hazardous waste	: Within the present knowledge hazardous waste, as defined		not regarded as
Date of issue/Date of revision	: 28-1-2024	Version :1	
Date of previous issue	: No previous validation	13/17	AkzoNobel

## **SECTION 13: Disposal considerations**

Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations.
	If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.
	For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	<ul> <li>Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.</li> </ul>
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

**14.6 Special precautions for : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not apaccording to IMOinstruments

: Not applicable.



AMBIANCE EAR WAT MIX BASE WITTE						
SECTION 15: Regulate	ory information					
15.1 Safety, health and enviror		gislation specific for th	e substance or m	ixture		
EU Regulation (EC) No. 1907/						
Annex XIV - List of substand Annex XIV None of the components are	-	ation				
	<u>Substances of very high concern</u> None of the components are listed.					
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	on the manufacture, placing on the market and use of certain dangerous substances,					
Other EU regulations						
VOC	: The provisions of Dire product label and/or te	ctive 2004/42/EC on VO echnical data sheet for fu		duct. Refer to the		
VOC for Ready-for-Use Mixture	: Not available.					
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Ozone depleting substances	<u>s (1005/2009/EU)</u>					
Not listed.						
Fire point						
Not listed.						
Persistent Organic Pollutant Not listed.	<u>ts</u>					
Seveso Directive						
This product is not controlled	under the Seveso Directi	ve.				
National regulations						
Product/ingredient name	List name	Name on list	Classification	Notes		
titanium dioxide	France Occupational Exposure Limits	titane (dioxyde de) en Ti	Carc. C2	-		
<b>Biocidal products regulation</b>	<u>n</u>					
Social Security Code, Articles L 461-1 to L 461-7						
Reinforced medical surveillance: Decree n ° 2012-135 of January 30, 2012 relating to the organization of occupational medicine: not applicable						
International regulations						
Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.						

## **Montreal Protocol**

Date of issue/Date of revision			
Date of previous issue			



## SECTION 15: Regulatory information

Not listed.

## Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical Safety :	No Chemical Safety Assessment has bee
------------------------	---------------------------------------

## Assessment

en carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
	VPVB = very Persistent and very bloaccumulative

## Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

## Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

## Full text of classifications [CLP/GHS]



**SECTION 16: Other information** 

	momaton
Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Carc. 2 Eye Dam. 1 Skin Corr. 1 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A Skin Sens. 1B	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SKIN SENSITIZATION - Category 1B
Date of printing Date of issue/ Date of	: 14-4-2024 : 28-1-2024
revision	
Date of previous issue	: No previous validation
Version	: 1
Unique ID	: DA7DF488320C1EEEAF86D2FDB948018E

## Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

